



## TECHNICAL DATA SHEET

ELECTRONIC TIMER	PRODUCT TYPE	
	ETR-1-OD	ETR-2-CY
SUPPLY VOLTAGE	24V - 230 V AC $\pm$ 20% , 50Hz	24V - 230 V AC $\pm$ 20% , 50Hz
	24V - 230 V DC $\pm$ 20%	24V - 230 V DC $\pm$ 20%
OUTPUT RELAY CONTACT	2 NO - 2NC ,5A @ 230 VAC (Resistive)	1NO - 1NC , 5A @ 230 VAC (Resistive)
TIME RANGE	0-3 secs, 0-30 secs. 0-3 mins, 0-30 mins.	0.5 secs & 3 secs.
OPERATING MODE	ON DELAY	CYCLIC
AMBIENT TEMPERATURE	-20 to 70°C	-20 to 70°C
TERMINALS	No. 14 AWG / 2.5 mm <sup>2</sup> Max 12-20 lb.in / 1.3-2.3 Nm	No. 14 AWG / 2.5 mm <sup>2</sup> Max 12-20 lb.in / 1.3-2.3 Nm
MOUNTING	M4 Screw & DIN Rail	M4 Screw & DIN Rail

**LAKSHMI ELECTRICAL CONTROL SYSTEMS, COIMBATORE**